

Lint Free!

SpliceMaster®

Dry Towelettes

For Cable Cleaning



FEATURES

- <u>NON-LINTING</u> Leaves no residue that could lead to tracking. Ideal for electrical cable splicing.
- <u>VERSATILE</u> Use to apply bulk SpliceMaster® Cleaners, or wipe them dry.
- THREE SIZES Choose 6" x 9", 8" x 12", or larger 12" x 12" size for big jobs.
- <u>TWO TYPES</u> Regular wipes (boxed) or apertured wipes (dispensing canister).
- DURABLE Won't shred under heavy wiping load.
- CONVENIENT Eliminates the need to search for rags.
- HANDY PACKAGING Perforation-cut for easy dispensing from box or canister.

SpliceMaster® Dry Towels are ideal for wiping excess solvent from electrical cables during splicing. This accelerates the evaporation rate of today's effective but slow-drying cleaners. Towelettes can also replace rags as a means of applying bulk solvent. Rags and other wipes are a poor choice for cable cleaning since they can deposit lint or other residues that can lead to tracking.

SpliceMaster® Dry Towels in the <u>DT-D65 canister package</u> are a slightly different style from the boxed wipes (DT-69 and DT-1212). The material is an apertured, spunlace polyester/woodpulp blend. DT-D65 wipes contain no binders or other chemical residues. They are durable with a high tensile strength in both directions. They have high absorbancy. The apertures (small holes or textured spaces) help grab and hold contaminants during the cleaning process. Non-linting, non-tearing, and non-snagging DT-D65 towelettes have an infinite number of uses beyond cable cleaning. The field-friendly self-dispensing plastic canister is durable, resealable, highly portable, and helps protect wipes from moisture, dust, bugs, and other grime--perfect for the service truck.

Catalog No.	Description	Units/CS	Image
DT-69	Box of 200 6" x 9" dry wipes.	1 200-count box	
DT-1212	Box of 100 12" x 12" dry wipes.	1 100-count box	None
DT-D65	Dispensing canister of 65 8" x 12" dry wipes.	6 canisters per box	Pilyment DY: D65

Copyright ©2010. American Polywater Corporation. All Rights Reserved

Important Notice: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from product's use, regardless of the legal theory asserted.



P.O. Box 53 Stillwater, MN 55082 U.S.A

custserv@polywater.com(e-mail) 1-800-328-9384 http://www.polywater.com(URL) fax 1-651-430-3634