

SAFETY DATA SHEET – SET

PowerPatch[®] Leak Repair Paste Kit

Product ID numbers: EP-KIT11, EP-KIT51, EP-KITB6, EP-KITB12,
EP-XXX (where XXX is the package code.)

Date Compiled: May 27, 2015



Supplier/Manufacturer:

American Polywater Corporation
11222 - 60th Street North
Stillwater, MN 55082 USA
Tel: 1-651-430-2270
Email: sds@polywater.com

Polywater Europe BV
Zuidhaven 9-11 Unit B2
4761 CR Zevenbergen
Netherlands
Tel: +31 (0)10 2330578
Email: sds@
polywater.com

Emergency telephone numbers

INFOTRAC 1-352-323-3500 (USA)

This product is a kit or a multi-part product with independent components. An SDS for each component is included. Do not separate SDSs.

Contains

EP-Paste A PowerPatch Sealant Part A SDS
EP-Paste B PowerPatch Sealant Part B SDS
EP-STICK PowerPatch Putty Stick SDS
RP Rapid Power Cleaning Wipe

Each Kit may or may not contain all SDS components

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

Product Name:
PowerPatch[®] Leak Repair EP Paste (Part A)
SEALANT 84191

Product ID numbers: EP-KIT11, EP-KIT51, EP-KITB6, EP-KITB12, EP-KITB12LA, EP-KITNB,
EP-BULKA36, EP-KIT05, EP-KITB12LV

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Sealant/adhesive resin, Part A of 2-Part Sealant

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation
11222 - 60th Street North
Stillwater, MN 55082 USA
Tel: 1-651-430-2270
Email: sds@polywater.com

1.4 Emergency telephone numbers

INFOTRAC 1-352-323-3500 (USA)

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to OSHA 29 CFR 1910.1200 and Regulation (EC) No 1272/2008.

Skin Irritation, Cat 2; H315

Eye Irritation, Cat 2A; H319

Skin Sensitization, Cat 1; H317

2.2 Label elements

Contains Bisphenol A-epichlorohydrin polymer



Pictograms:

Signal word: Warning

Hazard Statements:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary Statements:

P264 Wash thoroughly after handling.
P280 Wear protective gloves, protective clothing and eye protection.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P332 + P313 If skin irritation occurs: Get medical attention..

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
 P337 + P313 If eye irritation persists. Get medical attention.

2.3 Other hazards: No information available.

3. Composition/Information on Ingredients

| <u>Component</u> | <u>CAS #</u> | <u>EC #</u> | <u>Wt. %</u> | <u>GHS/CLP Classification</u> |
|-------------------------------------|--------------|-------------|--------------|---|
| Bisphenol A-epichlorohydrin polymer | 25068-38-6 | 500-033-5 | 30 - 50 | Skin Irrit 2, H315 Skin Sens 1, H317 Eye Irrit 2A, H319 |

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact: Immediately flush eyes with large quantity of water for 15 minutes. Seek medical attention.
Skin Contact: Remove contaminated clothing; flush skin thoroughly with soap and water for at least 15 minutes. If irritation or allergic reaction occurs, seek medical attention.
Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention.
Ingestion (Swallowing): No emergency medical treatment necessary

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

No information available.

5. Firefighting Measures

5.1 Extinguishing media:

Water fog or fine spray, dry chemical carbon dioxide, or foam.

5.2 Special hazards arising from the substance or mixture

Dense smoke is emitted when burned without sufficient oxygen.

Hazardous decomposition and by-products:

CO₂, CO, phenolics. May contain other combustion products of varying composition which may be toxic or irritating.

5.3 Advice for firefighters

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Water fog may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture. Direct water stream may spread fire.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate area. Use appropriate safety equipment.

6.2 Environmental precautions:

Avoid release to the environment. Prevent spill from entering drainage/sewer systems, waterways, basements or confined areas. Refer to Section 12 for more information.

6.3 Methods materials for containment and cleaning up:

Absorb spill with sand or absorbents. Residual resin may be removed using steam or hot soapy water. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Residual material can be removed with solvent.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Avoid personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

7.2 Conditions for safe storage, including incompatibilities

Keep containers cool, dry, and away from sources of ignition. Keep containers and cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

7.3 Specific end uses

See technical data sheet on this product for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations:

Contains no components with established Occupational Exposure Limit (OEL) values.

A Derived No Effect Level (DNEL) of 12.25 mg/m³ has been established for Acute Inhalation.

8.2 Exposure controls

Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced. Use a respirator or gas mask with cartridges for organic vapors (NIOSH or CE approved) with particulate pre-filter, P100 or AP2.

Protective gloves:

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include nitrile (included in most kits), neoprene, ethyl vinyl alcohol (EVAL), PVC. Use a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374). NOTE: The selection of specific glove for the application should account for other chemicals in the environment, physical requirements and potential user reaction to the glove material.

Eye protection:

Safety glasses recommended.

Other protective equipment:

Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

9. Physical and Chemical

9.1 Information of basic physical and chemical properties

| | |
|--|---------------------------|
| Appearance: | Dark gray or black paste. |
| Odor threshold: | Not available |
| pH: | Does not apply |
| Freezing point: | Not available |
| Boiling point: | Not available |
| Flash point: | >400°F / >200°C (PMCC) |
| Evaporation rate: | Not available |
| Flammability (solid, gas): | Not available |
| Upper/lower flammability or explosive limits: | Not available |
| Vapor pressure: | Not available |

| | |
|--|---------------|
| Vapor density (Air = 1): | >1 |
| Specific gravity (H₂O = 1): | 1.25 @ 25°C |
| Solubility in water: | Not available |
| Partition coefficient: n-octanol/water: | Not available |
| Auto-ignition temperature: | Not available |
| Decomposition temperature: | Not available |
| Viscosity: | Not available |

9.2 Other Information

| | |
|------------------------------|-------|
| Volatiles (Weight %): | 0% |
| VOC Content: | 0 g/l |

10. Stability and Reactivity

10.1 Reactivity:

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

Hazardous reactions will not occur under normal transport or storage conditions.

10.4 Conditions to avoid:

Avoid high temperatures above 300 °C (572 °F). Decomposition can occur above 350 °C (662 °F). Generation of gas during decomposition can cause pressure to build in closed systems.

10.5 Incompatible materials :

Strong acids or bases (especially primary or secondary aliphatic amines), strong oxidizing agents.

10.6 Hazardous decomposition products:

CO₂, CO, phenolics and other organic substances may be formed during combustion or elevated temperature degradation.

11. Toxicological Information

11.1 Information on toxicological effects:

Acute toxicity

Eye contact:

Direct eye contact with material or vapors may cause eye irritation.

Skin contact:

This product has moderate skin irritation potential. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material. Prolonged or repeated skin exposure may cause skin sensitization.

Irritation and Sensitization Potential:

May cause allergic skin reaction.

Inhalation (Breathing):

Low vapor pressure makes this route of exposure unlikely.

Ingestion:

Ingestion may cause irritation of the gastrointestinal tract.

Toxicity to Animals:

| | |
|-------------------------------|---|
| Bisphenol A Diglycidyl Ether: | LD ₅₀ (oral rat) >15,000 mg/kg |
| | LD ₅₀ (dermal rabbit) 23,000 mg/kg |

Aspiration Hazard:

No aspiration hazard expected.

Chronic Exposure:

Reproductive Toxicity: Not available.
Mutagenicity: Resins based on diglycidyl ether of bisphenol A have proved to be inactive when tested by in-vivo mutagenicity assays. These resins have shown activity in in-vitro microbial mutagenicity screening and have produced chromosomal aberrations in cultured rat-liver cells. The significance of these tests to humans is unknown.
Teratogenicity: Not available.
Specific Target Organ Toxicity (STOT): Not available.
Toxicologically Synergistic Products: Not available.
Carcinogenic Status: This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

12. Ecological Information

12.1 Toxicity:

Aquatic Toxicity: May be toxic to aquatic organisms.
 Bisphenol A Diglycidyl Ether: LC₅₀ (96 hr): 2 mg/l Oncorhynchus mykiss (rainbow trout) Semi-static test
 Bisphenol A Diglycidyl Ether: EC₅₀ (48 hr): 1.8 mg/l Daphnia magna (invertebrate) Static test
 Bisphenol A Diglycidyl Ether: ErC₅₀ (72 hr): 11 mg/l Fresh water algae (aquatic plants) Static test
 Bisphenol A Diglycidyl Ether: Chronic Toxicity Value: Daphnia magna (invertebrate), 21 d, number of offspring, NOEC: 0.3 mg/l Semi-static test

12.2 Persistence and degradability:

Bisphenol A Diglycidyl Ether: Based on stringent OECD test guidelines, this material cannot be considered readily biodegradable. Biodegradability depends on environmental conditions.
 Bisphenol A Diglycidyl Ether: OECD Biodegradation Test 302B 12% Biodegradation, 28 d exposure
 Bisphenol A Diglycidyl Ether: Theoretical Oxygen Demand 2.35 mg/mg

12.3 Bioaccumulation potential:

Bioconcentration potential is moderate.

12.4 Mobility in soil:

Potential for mobility in soil is low..

12.5 Results of PBT and vPvB Assessment:

This product is not, nor does it contain a substance that is a PBT or vPvB.

12.6 Other adverse effects:

None known.

13. Disposal Considerations

Do not dump into sewer, on ground or into any body of water. Dispose of product in accordance with National and Local Regulations.

14. Transport Information

DOT: Not Regulated
UN Number: 3077
UN Proper Shipping Name: Environmentally hazardous substance, solid, N.O.S. (Bisphenol A)
Class and Subsidiary Risk: 9
Packing Group: III

| | |
|--------------------------|--|
| ICAO/IATA-DGR: | Not Regulated (See Special Provision A197) |
| IMDG: | Not Regulated (See IMDG Code 2.10.2.7) |
| ADR/RID: | 9 |
| Other information | For surface shipments within the United States: Not regulated. |

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

USA Federal and State

All components are listed on the TSCA inventory.

| | | | | | |
|---|---------------------|----------------------|-------------------|-----------------------|-----------------------|
| Hazard Categories for SARA Section 311/312 Reporting | <u>Acute</u> Yes | <u>Chronic</u> No | <u>Fire</u> No | <u>Pressure</u> No | <u>Reactive</u> No |
|---|---------------------|----------------------|-------------------|-----------------------|-----------------------|

| | | | |
|--|---|----------------|------------------------------------|
| <u>Components</u> | CERCLA/SARA Sec 302 Hazardous Substance RQ | EHS TPQ | SARA Sec. 313 Toxic Release |
| The components of PowerPatch®-Leak Sealant Paste - Part A are not affected by these Superfund regulations. | | | |

| | | |
|----------------------|-------------|---|
| NFPA Ratings: | Health: | 1 |
| | Fire: | 1 |
| | Reactivity: | 1 |

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

European Union

All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. It does not contain Substances of Very High Concern (SVHC).

Canada

All components are listed on the DSL inventory. This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Classification: Class D, Division 2B

Australia

All components are listed on the AICS. Product is classified as hazardous according to criteria of NOHSC Australia.

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

16. Other Information

Abbreviations and acronyms:

- OSHA = Occupational Safety and Health Administration
- CLP = Classification, Labeling and Packaging Regulation
- STOT = Specific Target Organ Toxicity
- LD₅₀ = Median Lethal Dose
- DNEL = Derived No Effect Level
- ACGIH = American Conference of Governmental Industrial Hygienists
- TSCA = Toxic Substances Control Act (USA)
- DSL = Domestic Substances List (Canada)
- AICS = Australian Inventory of Chemical Substances

Hazard Statements:

| | |
|------|--------------------------------------|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |

| | |
|-------------------------------|--|
| Revision Date: | July 22, 2015 |
| Revision Number: | 6 |
| Supersedes: | January 2, 2015 |
| Other: | Not Applicable |
| Indication of Changes: | Section 1.1 product identifier updated in accordance with the provisions of OSHA 1910.1200 App D and REACH Annex II (EU No 453/2010). (GHS format) |

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

Product Name:
PowerPatch[®] Leak Repair EP Paste (Part B)
SEALANT 84193

Product ID numbers: EP-KIT11, EP-KIT51, EP-KITB6, EP-KITB12, EP-KITB12LA, EP-KITNB,
EP-BULK36, EP-KIT05, EP-KITB12LV

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Sealant/adhesive resin, Part B of 2-Part Sealant

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation
11222 - 60th Street North
Stillwater, MN 55082 USA
Tel: 1-651-430-2270
Email: sds@polywater.com

Polywater Europe BV
Zuidhaven 9-11 Unit B2
4761 CR Zevenbergen
Netherlands
Tel: +31 (0)10 2330578
Email: sds@ polywater.com

1.4 Emergency telephone numbers

INFOTRAC 1-352-323-3500 (USA)

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to OSHA 29 CFR 1910.1200 and Regulation (EC) No 1272/2008.

Skin Irritation, Cat 2

Eye Irritation, Cat 2

Skin Sensitization, Cat 1

2.2 Label elements

Contains:

Polymer of C-18 Unsaturated Fatty Acid Dimers, 1,3-bis[3-(Dimethylamino)propyl] urea, Triethylenetetramine, Diethylene glycol bis (3-aminopropyl) ether



Pictograms:

Signal word: Warning

Hazard Statements:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary Statements:

P264 Wash thoroughly after handling.
P280 Wear protective gloves, protective clothing and eye protection.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 If skin irritation occurs: Get medical attention.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
 P337 + P313 If eye irritation persists. Get medical attention.

2.3 Other hazards: No information available.

3. Composition/Information on Ingredients

| <u>Component</u> | <u>CAS #</u> | <u>EC #</u> | <u>Wt. %</u> | <u>GHS/CLP Classification</u> |
|--|--------------|-------------|--------------|---|
| Polymercaptan | Proprietary | -- | 30 - 40 | Skin Irrit 2, H315 Eye Dam 2, H319 |
| Polymer of C-18 Unsaturated Fatty Acid Dimers with TETA & TOFA | 68082-29-1 | 500-191-5 | 5 - 10 | Skin Irrit 2, H315 Skin Sens 1, H317 Eye Irrit 2A, H319 |
| 1,3-bis[3-(Dimethylamino)propyl] urea | 52338-87-1 | 257-861-2 | 2 - 5 | Skin Irrit 2, H315 Eye Dam 2, H319 |
| Polymer of C-18 Unsaturated Fatty Acid Dimers | 68541-13-9 | -- | 2 - 5 | Eye Irrit. 2, H319 |
| Triethylenetetramine | 112-24-3 | 203-950-6 | < 1 | Acute Tox. 4, H312 Skin Corr. 1AB, H314 Skin Sens. 1 H317 Aquatic Chronic 3 H412 |
| Diethylene glycol bis (3-aminopropyl) ether | 4246-51-9 | 224-207-2 | < 1 | Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Irrit 2, H319 |

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact: Immediately flush eyes with large quantity of water for 15 minutes. Seek medical attention.

Skin Contact: Remove contaminated clothing; flush skin thoroughly with soap and water for at least 15 minutes. If irritation or allergic reaction occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention.

Ingestion (Swallowing): Wash out mouth with water. Do not induce vomiting. If victim is unconscious, place on the left side with head down. Never give anything by mouth to an unconscious person. Do not leave victim unattended. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

No information available.

5. Firefighting Measures

5.1 Extinguishing media:

Water fog or fine spray, dry chemical carbon dioxide, or foam.

5.2 Special hazards arising from the substance or mixture

Dense smoke is emitted when burned without sufficient oxygen.

Hazardous decomposition and by-products:

Oxides of carbon, oxides of sulfur, oxides of nitrogen. May contain other combustion products of varying composition which may be toxic or irritating.

5.3 Advice for firefighters

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Water fog may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture. Direct water stream may spread fire.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate area. Use appropriate safety equipment.

6.2 Environmental precautions:

Avoid release to the environment. Refer to Section 12 for more information.

6.3 Methods materials for containment and cleaning up:

Absorb spill with sand or absorbents. Residual resin may be removed using steam or hot soapy water. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Residual material can be removed with solvent.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Avoid personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

7.2 Conditions for safe storage, including incompatibilities

Keep containers cool, dry, and away from sources of ignition. Keep containers and cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

7.3 Specific end uses

See technical data sheet on this product for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations:

Contains no components with established Occupational Exposure Limit (OEL) values.

8.2 Exposure controls

Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

Protective gloves:

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include nitrile (included in most kits), neoprene, ethyl vinyl alcohol (EVAL), PVC.

Eye protection:

Safety glasses recommended.

Other protective equipment:

Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

9. Physical and Chemical

9.1 Information of basic physical and chemical properties

| | |
|--|---|
| Appearance: | White to yellow paste; slight sulfur, pungent odor. |
| Odor threshold: | Not available |
| pH: | Does not apply |
| Freezing point: | Not available |
| Boiling point: | Not available |
| Flash point: | >200°F / >90°C (PMCC) |
| Evaporation rate: | Not available |
| Flammability (solid, gas): | Not available |
| Upper/lower flammability or explosive limits: | Not available |
| Vapor pressure: | <1 mm Hg @ 20°C |
| Vapor density (Air = 1): | Not available |
| Specific gravity (H₂O = 1): | 1.17 @ 20°C |
| Solubility in water: | Negligible |
| Partition coefficient: n-octanol/water: | Not available |
| Auto-ignition temperature: | Not available |
| Decomposition temperature: | Not available |
| Viscosity: | Not available |

9.2 Other Information

| | |
|------------------------------|-------|
| Volatiles (Weight %): | 0% |
| VOC Content: | 0 g/l |

10. Stability and Reactivity**10.1 Reactivity:**

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

Hazardous reactions will not occur under normal transport or storage conditions.

10.4 Conditions to avoid:

Avoid extreme heat and open flame.

10.5 Incompatible materials :

Strong oxidizing agents.

10.6 Hazardous decomposition products:

Oxides of carbon, oxides of sulfur, oxides of nitrogen and other organic substances may be formed during combustion or elevated temperature degradation.

11. Toxicological Information**11.1 Information on toxicological effects:****Acute toxicity****Eye contact:**

Direct eye contact with material or vapors may cause eye irritation.

Skin contact:

May cause severe skin irritation, especially on prolonged contact. Prolonged or repeated skin exposure may

cause skin sensitization.

Irritation and Sensitization Potential:

This product has high skin irritation potential. It is a sensitizer.

Inhalation (Breathing):

Low vapor pressure makes this route of exposure unlikely. No known significant hazard.

Ingestion:

Material is considered slightly toxic. Ingestion may cause irritation of the gastrointestinal tract, nausea, vomiting, and diarrhea.

Toxicity to Animals:

| | |
|---|---|
| Polymercaptan amine blend | LD ₅₀ (oral rat) >2,000 mg/kg |
| Polymer of C-18 Unsaturated Fatty Acid Dimers with TETA & TOFA | LD ₅₀ (oral rat) >2,000 mg/kg LD ₅₀ (dermal rabbit) >2,000 mg/kg |
| Triethylenetetramine | LD ₅₀ (oral rat) 2,780 mg/kg LD ₅₀ (dermal rabbit) 550 mg/kg |

Aspiration Hazard:

No aspiration hazard expected.

Chronic Exposure:

Reproductive Toxicity: Not available.

Mutagenicity: Not available.

Teratogenicity: Not available.

Specific Target Organ Toxicity (STOT) Not available.

Toxicologically

Synergistic Products: Not available.

Carcinogenic Status: This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

12. Ecological Information

12.1 Toxicity:

Aquatic Toxicity: Not available.

12.2 Persistence and degradability: Not available.

12.3 Bioaccumulation potential: Not available.

12.4 Mobility in soil: Not available.

12.5 Results of PBT and vPvB Assessment: This product is not, nor does it contain a substance that is a PBT or vPvB.

12.6 Other adverse effects: None known.

13. Disposal Considerations

Do not dump into sewer, on ground or into any body of water. Dispose of product in accordance with National and Local Regulations.

14. Transport Information

DOT: Not Regulated

UN Number: Not Listed

UN Proper Shipping Name: Not Applicable

Class and Subsidiary Risk: Not Applicable

Packing Group: Not Applicable

ICAO/IATA-DGR: Not Regulated
 IMDG: Not Regulated
 ADR/RID: Not Regulated

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

USA Federal and State

All components are listed on the TSCA inventory.

| | | | | | |
|---|---------------------|----------------------|-------------------|-----------------------|-----------------------|
| Hazard Categories for SARA Section 311/312 Reporting | <u>Acute</u> Yes | <u>Chronic</u> No | <u>Fire</u> No | <u>Pressure</u> No | <u>Reactive</u> No |
|---|---------------------|----------------------|-------------------|-----------------------|-----------------------|

| | | | |
|--|---|----------------|--|
| Components | CERCLA/SARA Sec 302 Hazardous Substance RQ | EHS TPQ | SARA Sec. 313 Toxic Release |
| The components of PowerPatch®-Leak Sealant Paste - Part B are not affected by these Superfund regulations. | | | |

NFPA Ratings:

| | |
|-------------|---|
| Health: | 2 |
| Fire: | 1 |
| Reactivity: | 1 |

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

European Union

All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. It does not contain Substances of Very High Concern (SVHC).

Canada

All components are listed on the DSL inventory. This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Classification: Class D, Division 2B

Australia

All components are listed on the AICS. Product is classified as hazardous according to criteria of NOHSC Australia.

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

16. Other Information

Abbreviations and acronyms:

- OSHA = Occupational Safety and Health Administration
- CLP = Classification, Labeling and Packaging Regulation
- STOT = Specific Target Organ Toxicity
- LD₅₀ = Median Lethal Dose
- DNEL = Derived No Effect Level
- ACGIH = American Conference of Governmental Industrial Hygienists
- TSCA = Toxic Substances Control Act (USA)
- DSL = Domestic Substances List (Canada)
- AICS = Australian Inventory of Chemical Substances

Hazard Statements:

| | |
|------|--------------------------------------|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |

| | |
|-------------------------------|--|
| Revision Date: | July 22, 2015 |
| Revision Number: | 5 |
| Supersedes: | January 2, 2015 |
| Other: | Not Applicable |
| Indication of Changes: | Section 1.1 product identifier updated in accordance with the provisions of OSHA 1910.1200 App D and REACH Annex II (EU No 453/2010). (GHS format) |

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

Product Name:
PowerPatch[®] Putty Stick (EP-STICK)
Part Numbers: 50822, 51043

Product ID numbers: EP-STICK4;
Contained in EP-KIT11, EP-KIT51, EP-KITB6, EP-KITB12, EPCT-KIT1, EPCT-KITB6;
EP-XXX and EPCT-XXX (Where XXX is the package code.)

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: 2-Part Putty Sealant for temporary repair

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation
11222 - 60th Street North
Stillwater, MN 55082 USA
Tel: 1-651-430-2270
Email: sds@polywater.com

1.4 Emergency telephone numbers

INFOTRAC 1-352-323-3500 (USA)

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to OSHA 29 CFR 1910.1200 and Regulation (EC) No 1272/2008.

Skin Irritation, Cat 2; H315
Eye Irritation, Cat 2B; H319
Skin Sensitization, Cat 1; H317

2.2 Label elements

Contains Bisphenol A-epichlorohydrin polymer



Pictograms:

Signal word: Warning

Hazard Statements:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary Statements:

P264 Wash thoroughly after handling.
P280 Wear protective gloves, protective clothing and eye protection.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 If skin irritation occurs: Get medical attention..
 P305 + P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
 P338
 P337 + P313 If eye irritation persists. Get medical attention.

2.3 Other hazards: No information available.

3. Composition/Information on Ingredients

| <u>Component</u> | <u>CAS #</u> | <u>EC #</u> | <u>Wt. %</u> | <u>GHS/CLP Classification</u> |
|-------------------------------------|--------------|-------------|--------------|---|
| Bisphenol A-epichlorohydrin polymer | 25068-38-6 | 500-033-5 | 10 - 30 | Skin Irrit 2, H315 Skin Sens 1, H317 Eye Irrit 2A, H319 |

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact: Immediately flush eyes with large quantity of water for 15 minutes. Seek medical attention.
Skin Contact: Remove contaminated clothing; flush skin thoroughly with soap and water for at least 15 minutes. If irritation or allergic reaction occurs, seek medical attention.
Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention.
Ingestion (Swallowing): No emergency medical treatment necessary

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

No information available.

5. Firefighting Measures

5.1 Extinguishing media:

Water fog or fine spray, dry chemical carbon dioxide, or foam.

5.2 Special hazards arising from the substance or mixture

Dense smoke is emitted when burned without sufficient oxygen.

Hazardous decomposition and by-products:

CO₂, CO, phenolics. May contain other combustion products of varying composition which may be toxic or irritating.

5.3 Advice for firefighters

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Water fog may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture. Direct water stream may spread fire.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate area. Use appropriate safety equipment.

6.2 Environmental precautions:

Avoid release to the environment. Prevent spill from entering drainage/sewer systems, waterways, basements or confined areas. Refer to Section 12 for more information.

6.3 Methods materials for containment and cleaning up:

Absorb spill with sand or absorbents. Residual resin may be removed using steam or hot soapy water. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Residual material can be removed with solvent.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage**7.1 Precautions for safe handling**

Avoid personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

7.2 Conditions for safe storage, including incompatibilities

Keep containers cool, dry, and away from sources of ignition. Keep containers and cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

7.3 Specific end uses

See technical data sheet on this product for further information.

8. Exposure Controls / Personal Protection**8.1 Control parameters****Exposure limits and recommendations:**

Contains no components with established Occupational Exposure Limit (OEL) values.

A Derived No Effect Level (DNEL) of 12.25 mg/m³ has been established for Acute Inhalation.

8.2 Exposure controls**Respiratory protection:**

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced. Use a respirator or gas mask with cartridges for organic vapors (NIOSH or CE approved) with particulate pre-filter, P100 or AP2.

Protective gloves:

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include nitrile (included in most kits), neoprene, ethyl vinyl alcohol (EVAL), PVC. Use a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374). NOTE: The selection of specific glove for the application should account for other chemicals in the environment, physical requirements and potential user reaction to the glove material.

Eye protection:

Safety glasses recommended.

Other protective equipment:

Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

9. Physical and Chemical**9.1 Information of basic physical and chemical properties**

| | |
|--|--|
| Appearance: | Gray/dark gray, solid putty stick. Pungent, sulfurous odor. |
| Odor threshold: | Not available |
| pH: | Not available |
| Freezing point: | Not available |
| Boiling point: | Not available |
| Flash point: | >199.9°F / >93.3°C (PMCC) |
| Evaporation rate: | Not available |
| Flammability (solid, gas): | Not available |
| Upper/lower flammability or explosive limits: | Not available |

| | |
|--|-----------------------------|
| Vapor pressure: | Not available |
| Vapor density (Air = 1): | Not available |
| Specific gravity (H₂O = 1): | 2.247 |
| Solubility in water: | Not available |
| Partition coefficient: n-octanol/water: | Not available |
| Auto-ignition temperature: | Not available |
| Decomposition temperature: | >392°F / >200°C |
| Viscosity: | Not available (thick putty) |

9.2 Other Information

| | |
|------------------------------|-------|
| Volatiles (Weight %): | <0.1% |
| VOC Content: | 0 g/l |

10. Stability and Reactivity

10.1 Reactivity:

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

Hazardous reactions will not occur under normal transport or storage conditions.

10.4 Conditions to avoid:

Avoid high temperatures above 300 °C (572 °F). Decomposition can occur above 350 °C (662 °F). Generation of gas during decomposition can cause pressure to build in closed systems.

10.5 Incompatible materials :

Strong acids or bases (especially primary or secondary aliphatic amines), strong oxidizing agents.

10.6 Hazardous decomposition products:

CO₂, CO, phenolics and other organic substances may be formed during combustion or elevated temperature degradation.

11. Toxicological Information

11.1 Information on toxicological effects:

Acute toxicity

Eye contact:

Direct eye contact with material or vapors may cause eye irritation.

Skin contact:

This product has moderate skin irritation potential. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material. Prolonged or repeated skin exposure may cause skin sensitization.

Irritation and Sensitization Potential:

May cause allergic skin reaction.

Inhalation (Breathing):

Low vapor pressure makes this route of exposure unlikely.

Ingestion:

Ingestion may cause irritation of the gastrointestinal tract.

Toxicity to Animals:

| | |
|-------------------------------|---|
| Bisphenol A Diglycidyl Ether: | LD ₅₀ (oral rat) >15,000 mg/kg |
| | LD ₅₀ (dermal rabbit) 23,000 mg/kg |

Aspiration Hazard:

No aspiration hazard expected.

Chronic Exposure:

Reproductive Toxicity: Not available.
Mutagenicity: Resins based on diglycidyl ether of bisphenol A have proved to be inactive when tested by in-vivo mutagenicity assays. These resins have shown activity in in-vitro microbial mutagenicity screening and have produced chromosomal aberrations in cultured rat-liver cells. The significance of these tests to humans is unknown.
Teratogenicity: Not available.
Specific Target Organ Toxicity (STOT) Not available.
Toxicologically Synergistic Products: Not available.
Carcinogenic Status: This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

12. Ecological Information

12.1 Toxicity:

Aquatic Toxicity: May be toxic to aquatic organisms.
 Bisphenol A Diglycidyl Ether: LC₅₀ (96 hr): 2 mg/l Oncorhynchus mykiss (rainbow trout) Semi-static test
 Bisphenol A Diglycidyl Ether: EC₅₀ (48 hr): 1.8 mg/l Daphnia magna (invertebrate) Static test
 Bisphenol A Diglycidyl Ether: ErC₅₀ (72 hr): 11 mg/l Fresh water algae (aquatic plants) Static test
 Bisphenol A Diglycidyl Ether: Chronic Toxicity Value: Daphnia magna (invertebrate), 21 d, number of offspring, NOEC: 0.3 mg/l Semi-static test

12.2 Persistence and degradability:

Bisphenol A Diglycidyl Ether: Based on stringent OECD test guidelines, this material cannot be considered readily biodegradable. Biodegradability depends on environmental conditions.
 Bisphenol A Diglycidyl Ether: OECD Biodegradation Test 302B 12% Biodegradation, 28 d exposure
 Bisphenol A Diglycidyl Ether: Theoretical Oxygen Demand 2.35 mg/mg

12.3 Bioaccumulation potential:

Bioconcentration potential is moderate.

12.4 Mobility in soil:

Potential for mobility in soil is low..

12.5 Results of PBT and vPvB Assessment:

This product is not, nor does it contain a substance that is a PBT or vPvB.

12.6 Other adverse effects:

None known.

13. Disposal Considerations

Do not dump into sewer, on ground or into any body of water. Dispose of product in accordance with National and Local Regulations.

14. Transport Information

DOT: Not Regulated
UN Number: 3077
UN Proper Shipping Name: Environmentally hazardous substance, solid, N.O.S. (Bisphenol A)
Class and Subsidiary Risk: 9
Packing Group: III

| | |
|--------------------------|--|
| ICAO/IATA-DGR: | Not Regulated (See Special Provision A197) |
| IMDG: | Not Regulated (See IMDG Code 2.10.2.7) |
| ADR/RID: | 9 |
| Other information | For surface shipments within the United States: Not regulated. |

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

USA Federal and State

All components are listed on the TSCA inventory.

| | | | | | |
|---|---------------------|-----------------------|-------------------|-----------------------|-----------------------|
| Hazard Categories for SARA Section 311/312 Reporting | <u>Acute</u> Yes | <u>Chronic</u> Yes | <u>Fire</u> No | <u>Pressure</u> No | <u>Reactive</u> No |
|---|---------------------|-----------------------|-------------------|-----------------------|-----------------------|

| | | | |
|---|---|----------------|------------------------------------|
| <u>Components</u> | CERCLA/SARA Sec 302 Hazardous Substance RQ | EHS TPQ | SARA Sec. 313 Toxic Release |
| Components are not affected by these Superfund regulations. | | | |

| | | |
|----------------------|-------------|---|
| NFPA Ratings: | Health: | 2 |
| | Fire: | 1 |
| | Reactivity: | 0 |

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

European Union

All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. It does not contain Substances of Very High Concern (SVHC).

Canada

All components are listed on the DSL inventory. This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Classification: Class D, Division 2B

Australia

All components are listed on the AICS. Product is classified as hazardous according to criteria of NOHSC Australia.

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

16. Other Information

Abbreviations and acronyms:

- OSHA = Occupational Safety and Health Administration
- CLP = Classification, Labeling and Packaging Regulation
- STOT = Specific Target Organ Toxicity
- LD₅₀ = Median Lethal Dose
- DNEL = Derived No Effect Level
- ACGIH = American Conference of Governmental Industrial Hygienists
- TSCA = Toxic Substances Control Act (USA)
- DSL = Domestic Substances List (Canada)
- AICS = Australian Inventory of Chemical Substances

Hazard Statements:

| | |
|------|--------------------------------------|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |

| | |
|-------------------------------|--|
| Revision Date: | July 22, 2015 |
| Revision Number: | 6 |
| Supersedes: | November 25, 2014 |
| Other: | Not Applicable |
| Indication of Changes: | Section 1.1 product identifier updated in accordance with the provisions of OSHA 1910.1200 App D and REACH Annex II (EU No 453/2010). (GHS format) |

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

**Product Name: Type RP™
Rapid Power Electrical Cleaning Wipe**

Product ID numbers: RP-1, RP-1L
RP-XXX (Where XXX is the package code.)

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Utility Cleaner/Degreaser

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation
11222 - 60th Street North
Stillwater, MN 55082 USA
Tel: 1-651-430-2270
Email: sds@polywater.com

Polywater Europe BV
Zuidhaven 9-11 Unit B2
4761 CR Zevenbergen
Netherlands
Tel: +31 (0)10 2330578
Email: sds@ polywater.com

1.4 Emergency telephone numbers

INFOTRAC 1-352-323-3500 (USA)

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to OSHA 29 CFR 1910.1200 and Regulation (EC) No 1272/2008.

| | |
|---------------|------|
| Flam Liq 2 | H225 |
| Skin Irrit. 2 | H315 |
| STOT SE 3 | H336 |

2.2 Label elements

Contains: 2-methylpentane, Low boiling point naphtha, 1-methoxypropan-2-ol



Pictograms:

Signal word: Danger

Hazard Statements:

| | |
|------|--------------------------------------|
| H225 | Extremely flammable liquid and vapor |
| H315 | Causes skin irritation. |
| H336 | May cause drowsiness or dizziness |

Precautionary Statements:

| | |
|-------------|--|
| P210 | Keep away from sparks, flames and hot surfaces. No smoking. |
| P261 | Avoid breathing vapor. |
| P280 | Wear protective gloves. |
| P304 + P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |

P303 + P361 + P353 IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water.
 P370 + P378 In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction.
 P403 + P235 Store in a well-ventilated place. Keep cool.

Notes: Aspiration classification not applied due to the physical form of the product.

2.3 Other hazards: No information available.

3. Composition/Information on Ingredients

| <u>Component</u> | <u>CAS #</u> | <u>EC #</u> | <u>Wt. %</u> | <u>GHS/CLP Classification</u> |
|---------------------------|--------------|-------------|--------------|--|
| 2-methylpentane | 107-83-5 | 203-523-4 | 40 - 60% | Flam Liq 2, H225; Asp Tox 1, H304; Skin Irrit 2, H315 STOT SE 3, H336 |
| Low boiling point naphtha | 64742-89-8 | 265-192-2 | 40 - 60% | Flam Liq 2, H225; Asp Tox 1, H304; Skin Irrit 2, H315 STOT SE 3, H336 |
| 1-methoxypropan-2-ol | 107-98-2 | 203-539-1 | <10% | Flam Liq 3, H226; STOT SE 3, H336 |

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact: If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.

Skin Contact: Remove contaminated clothing; flush skin thoroughly with water. If irritation occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention. If breathing is difficult, provide oxygen. If not breathing, give artificial respiration. Seek immediate medical attention.

Ingestion (Swallowing): Do not induce vomiting or give anything by mouth unless directed to do so by medical personnel. Get medical attention if symptoms appear.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

No information available.

5. Firefighting Measures

5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition and by-products:

Burning generates carbon monoxide, carbon dioxide.

5.3 Advice for firefighters

Wear appropriate, protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. For a spill in a confined space, provide mechanical ventilation to disperse or exhaust vapors. For emergency responders: use respiratory protection: half-face or full-face respirator with filter(s) for organic vapor for spills in a confined space. Chemical goggles are recommended if splashes or contact with eyes is possible. For small spills: normal antistatic work clothes are usually adequate.

6.2 Environmental precautions:

Avoid release to the environment.

6.3 Methods materials for containment and cleaning up:

Collect towel and absorb any excess material with sand or absorbents.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use only outdoors or in a well-ventilated area. For industrial or professional use only.

7.2 Conditions for safe storage, including incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

7.3 Specific end uses

See technical data sheet on this product for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations:

| Component Name | Limit | | Standard | Source/Note |
|---------------------------|---------------------------|-------------------------|-------------|-------------|
| 2-methylpentane | TLV | 500 ppm | ACGIH, OSHA | USA |
| | | 100 ppm | | |
| | TLV | 1,800 mg/m ³ | NIOSH | USA |
| | STEL | 1,000 ppm | ACGIH, OSHA | |
| Low boiling point naphtha | No information available. | | | |
| 1-methoxypropan-2-ol | TWA | 100 ppm | ACGIH | USA |
| | STEL | 150 ppm | ACGIH | USA |

8.2 Exposure controls

Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Suggested Material: Nitrile Rubber

For short term contact (<15 minutes), splashes use 0.2 mm. For full contact use

Suggested Thickness: 0.4 mm

Exact break-through time has not been determined. Guidance is based on similar chemistry/material.

Maximum wearing time should be determined based on 50 % of the penetration time determined by EN

374 part III.

Eye protection:

Safety glasses recommended.

Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

9. Physical and Chemical

9.1 Information of basic physical and chemical properties

| | |
|---|-------------------------------------|
| Appearance: | Clear, colorless liquid; mild odor. |
| Odor threshold: | Not available |
| pH: | Does not apply |
| Freezing point: | Not available |
| Boiling point: | 144°F / 62°C (initial) |
| Flash point: | 19°F / -7°C (TCC) |
| Evaporation rate: | >2 (n-butyl acetate = 1) |
| Flammability (solid, gas): | Not applicable to liquids |
| Flammability limits: | LEL: 1.2% |
| Vapor pressure: | Not available |
| Vapor density (Air = 1): | >1(Air = 1) |
| Specific gravity (H₂O = 1): | 0.72 |
| Solubility in water: | Not available |
| Coefficient of Water/Oil Distribution: | Not available |
| Auto-ignition temperature: | Not available |
| Decomposition temperature: | Not available |
| Viscosity: | Not available |

9.2 Other Information

| | |
|------------------------------|---------|
| Volatiles (Weight %): | 100% |
| VOC Content: | 720 g/l |

10. Stability and Reactivity

10.1 Reactivity:

See remaining headings in Section 10.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

None known.

10.4 Conditions to avoid:

Avoid heat, flame, and sparks.

10.5 Incompatible materials :

Strong oxidizing agents.

10.6 Hazardous decomposition products:

Carbon dioxide, carbon monoxide.

11. Toxicological Information

11.1 Information on toxicological effects:**Acute toxicity****Eye contact:**

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

Skin contact:

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

Irritation and Sensitization Potential:

Product may be irritating to skin and eyes. It is not a sensitizer.

Inhalation (Breathing):

Concentrated solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

Toxicity to Animals:

| | |
|---------------------------|---|
| 2-methylpentane | No Data Available |
| Low boiling point naphtha | LD ₅₀ (oral rat) >5,000 mg/kg LD ₅₀ (dermal rabbit) >2,000 mg/kg Rabbit 4 hr exposure: Irritating to skin, irritating to eyes |
| 1-methoxypropan-2-ol | LD ₅₀ (oral rat) 6,100 mg/kg LD ₅₀ (dermal rabbit) 13,000 mg/kg LC ₅₀ (inhl rat) >6 mg/l |

Chronic Exposure:

Reproductive Toxicity: No data available.

Mutagenicity: No data available

Teratogenicity: No data available

Specific Target Organ Toxicity (STOT) No end point data.

Toxicologically Synergistic Products: Not available.

Carcinogenic Status:

IARC No components of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC.

OSHA No components of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP No components of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

12. Ecological Information**12.1 Ecotoxicity:****Aquatic Toxicity:**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2-methylpentane

No Data Available

Low boiling point naphtha

96 h LC₅₀ Oncorhynchus mykiss (Rainbow Trout) 8.2 mg/l

48 h EC₅₀ Daphnia magna (water flea) 4.5 mg/l

96 h EC₅₀ Pseudokirchneriella subcapitata (green algae) 3.7 mg/l

1-methoxypropan-2-ol

96 h LC₅₀ Pimephales promelas (Fathead Minnow) 20,800 mg/l

| | |
|---|--|
| | 48 h LC ₅₀ Daphnia magna (water flea) 23,300 mg/l |
| | 7 d EC ₅₀ Pseudokirchneriella subcapitata (green algae) > 1000 mg/l |
| 12.2 Persistence and degradability: | Expected to be biodegradable |
| Low boiling point naphtha | 77% biodegradable, 28 d exposure time, method: OECD 301E |
| 1-methoxypropan-2-ol | 96% biodegradable, 28 d exposure time, method: OECD 301E |
| 12.3 Bioaccumulation potential: | No information available |
| 12.4 Mobility in soil: | No information available |
| 12.5 Results of PBT and vPvB Assessment: | This product is not, nor does it contain a substance that is a PBT or vPvB. |
| 12.6 Other adverse effects: | None known. |

13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

14. Transport Information

| | |
|---|--|
| US DOT Domestic Ground Transportation: | Not Regulated (See Special Provision 47). |
| UN Number: | 3175 |
| UN Proper shipping name: | Solids Containing Flammable Liquid, N.O.S., (Contains: 2-methylpentane, Low boiling point naphtha) |
| Transport hazard class(es): | Class 4.1 |
| Packing group: | II |
| Environmental hazards: | None known |
| Special precautions: | None known |
| ICAO/IATA-DGR: | Not Regulated (See Special Provision A46) |
| IMDG: | Not Regulated (See Special Provision 216) |

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

USA Federal and State

All components are listed on the TSCA inventory.

| | | | | | |
|---|---------------------|-----------------------|--------------------|-----------------------|-----------------------|
| Hazard Categories for SARA Section 311/312 Reporting | <u>Acute</u> Yes | <u>Chronic</u> Yes | <u>Fire</u> Yes | <u>Pressure</u> No | <u>Reactive</u> No |
|---|---------------------|-----------------------|--------------------|-----------------------|-----------------------|

| | | | |
|---|---|----------------|--|
| <u>Components</u> | CERCLA/SARA Sec 302 <u>Hazardous Substance RQ</u> | <u>EHS TPQ</u> | SARA Sec. 313 <u>Toxic Release</u> |
| Components are not affected by these Superfund regulations. | | | |

| | | |
|----------------------|-------------|---|
| NFPA Ratings: | Health: | 2 |
| | Fire: | 3 |
| | Reactivity: | 0 |

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

European Union

All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. It does not contain Substances of Very High Concern (SVHC).

Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

WHMIS Classification: B2

Australia

All components are listed on the AICS.

Hazardous according to criteria of NOHSC Australia.

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier

16. Other Information

Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration

CLP = Classification, Labeling and Packaging Regulation

STOT = Specific Target Organ Toxicity

LD₅₀ = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

| | |
|-------------------------------|---|
| Revision Date: | April 23, 2015 |
| Revision Number: | 1 |
| Supersedes: | -- |
| Other: | Not Applicable |
| Indication of Changes: | Created in accordance with the provisions of OSHA 1910.1200 App D and REACH Annex II (EU No 453/2010). (GHS format) |

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.