SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

Product Name: HydraSol[®] Cable Gel Remover Saturated Wipe or Towel Package

Product ID numbers: HS-1, HS-1C, HS-1M, HS-1D42, HS-D72, HS-D72C

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses:	Removing cable filling greases

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation 11222 - 60th Street North P.O. Box 53 Stillwater, MN 55082 USA Tel: 1-651-430-2270 Email: custserv@polywater.com Polywater Europe BV Zuidhaven 9-11 Unit B2 4761 CR Zevenbergen Netherlands Tel: +31 (0)10 2330578 Email: custserv@polywater.com

1.4 Emergency telephone numbers

USA
+1-651-430-2270

Europe +31 (0)10 2330578

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to OSHA 29 CFR 1910.1200 and Regulation (EC) No 1272/2008.

Asp Tox 1	H304
Skin Irrit 3	H316
Flam Liq 4	H227

2.2 Label elements



Pictograms:		
Signal word:	Danger	
Hazard Statements:		
H227	Combustible liquid	
H304	May be fatal if swallowed and enters airways	
H316	Causes mild skin irritation	
Precautionary Statements:		
P210	Keep away from flames and hot surfaces. No smoking.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	

- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P331 Do NOT induce vomiting.

P332 + P313	If skin irritation occurs: Get medical advice/attention
P403 + P235	Store in a well-ventilated place. Keep cool.
2.3 Other hazards:	No information available.

3. Composition/Information on Ingredients				
<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>	GHS/CLP Classification Asp. Tox. 1 H304;
Medium Aliphatic				EUH066 Skin Irrit. 3 H316;
Petroleum Solvent	64742-47-8	265-149-8	< 25	Flam Liq 4 H227
Citrus Terpenes	94266-47-4	304-454-3	< 25	

This product contains no other reportable hazardous components under OSHA 29 CFR 1910.1200 and European Regulation (EC) No 1272/2008.

4. First Aid Measures

4.1 Description of first aid measures

2

Eye Contact:	If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.
Skin Contact:	Remove contaminated clothing; flush skin thoroughly with water. If irritation occurs, seek medical attention.
Inhalation (Breathing):	If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention. If breathing is difficult, provide oxygen. If not breathing, give artificial respiration. Seek immediate medical attention.
Ingestion (Swallowing):	Do not induce vomiting or give anything by mouth. If victim is drowsy or unconscious, place on the left side with head down. Do not leave victim unattended. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

Aspiration hazard. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis.

5. Firefighting Measures

5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition and by-products:

Burning generates CO, CO₂ and smoke. Smoke may be acrid and fumes irritating.

5.3 Advice for firefighters

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Limited spill hazard with saturated towel package.

6.2 Environmental precautions:

Avoid release to the environment.

6.3 Methods materials for containment and cleaning up:

Collect towel and absorb any excess material with sand or absorbents.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2 Conditions for safe storage, including incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

7.3 Specific end uses

See technical data sheet on this product for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations:

Component Name	Limit	Standard	Source/Note	
Medium Aliphatic Petroleum Solven	t 100 ppm	ACGIH TWA	United States	
Medium Aliphatic Petroleum Solven	t 500 ppm	OSHA TWA	United States	
Medium Aliphatic Petroleum Solven	t 1200 mg/m3	RCP* TWA	ACGIH, Manufacturer	

*reciprocal calculation procedure for total hydrocarbons

8.2 Exposure controls

Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Eye protection:

Safety glasses recommended.

Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

9. Physical and Chemical

9.1 Information of basic physical and chemical properties (bulk liquid)

Appearance:	Milky-white liquid with light citrus scent.
Odor threshold:	Not available
pH:	Neutral
Freezing point:	Not available
Boiling point:	212°F (100°C) Initial
Flash point:	155°F (68°C), Closed Cup (PMCC)
Evaporation rate:	<0.06 (n-butyl acetate = 1)

Flammability (solid, gas): Upper/lower flammability or	Not applicable to liquids
explosive limits:	Not available
Vapor pressure:	10.5 mm Hg @ 20°C
Vapor density (Air = 1):	Not available
Specific gravity (H ₂ O = 1):	0.91
Solubility in water:	Dilutes emulsion
Partition coefficient: n-	
octanol/water:	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
Viscosity:	Not available
9.2 Other Information	
Volatiles (Weight %):	>97%
VOC Content:	375 g/l

10. Stability and Reactivity

10.1 Reactivity:

See remaining headings in Section 10.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

None known.

10.4 Conditions to avoid:

Avoid heat, flame, and sparks.

10.5 Incompatible materials :

Strong oxidizing agents.

10.6 Hazardous decomposition products:

Carbon dioxide, carbon monoxide.

11. Toxicological Information

11.1 Information on toxicological effects: Acute toxicity

Eve contact:

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

Skin contact:

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

Irritation and Sensitization Potential:

Product may be irritating to skin and eyes. It is not a sensitizer.

Inhalation (Breathing):

Concentrated petroleum solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue). Persons with impaired lung function may experience additional breathing difficulties due to the irritant properties of this material.

Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

Toxicity to Animals: Medium Aliphatic	
PetroleumSolvent:	LD ₅₀ (oral rat) >5000 mg/kg
	LD ₅₀ (dermal rabbit) >2000 mg/kg
	LC ₅₀ (inhl rat) >4.3mg/L, 4 hours
Citrus Terpenes:	LD ₅₀ (oral rat) >5000 mg/kg
	LD ₅₀ (dermal rabbit) 5000 mg/kg
	RD ₅₀ 1000 ppm
Aspiration hazard	
May be fatal if swallowed and e	enters airways. Based on physico-chemical properties of the material.
Chronic Exposure:	
Reproductive Toxicity:	Not available.
Mutagenicity:	Not available.
Teratogenicity:	Not available.
Specific Target Organ	No and point data
Toxicity (STOT)	No end point data.
Toxicologically Synergistic Products:	Not available.
Carcinogenic Status:	This substance has not been identified as a carcinogen or probable

12. Ecological Information

12.1	Toxicity:	

Ecotoxicity:	No information available.
Aquatic Toxicity:	No information available.
12.2 Persistence and degradability:	Expected to be biodegradable.
12.3 Bioaccumulation potential:	No information available
12.4 Mobility in soil:	No information available.
12.5 Results of PBT and vPvB Assessment:	This product is not, nor does it contain a substance that is a PBT or vPvB.
12.6 Other adverse effects:	None known.

carcinogen by NTP, IARC, or OSHA, nor have any of its components.

13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

14. Transport Information

UN Number:	Not Listed
UN Proper shipping name:	Not Applicable
Transport hazard class(es):	Not Applicable
Packing group:	Not Applicable
Environmental hazards:	None known
Special precautions:	None known
TDG:	Not Regulated
ICAO/IATA-DGR:	Not Regulated
IMDG:	Not Regulated
ADR/RID:	Not Regulated

15. Regulatory Information

USA Federal and State

All components are listed on the TSCA inventory.

Hazard Categories for	SARA	<u>Acute</u>	<u>Chronic</u>	Fire	Pressure	Reactive
Section 311/312 Repo	rting	No	No	Yes	No	No
CERCLA/SARA Sec 302 SARA Sec. 313						
Components	<u>Hazar</u>	dous Subst	<u>ance RQ</u>	<u>EHS TPQ</u>	<u>Toxic</u>	<u>Release</u>
Components are not affected by these Superfund regulations						

Components are not affected by these Superfund regulations.

NFPA Ratings:	Health:	1
-	Fire:	2
	Reactivity:	0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

European Union

All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. It does not contain Substances of Very High Concern (SVHC).

Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Classification:

Australia

All components are listed on the AICS. Hazardous according to criteria of NOHSC Australia. Product classified as harmful (Xn).

B3

ontact Information: ADAPT Australia Pty. Ltd. 11 - 19 Global Drive	
	Tullamarine Victoria 3043 Telephone Number. 03 9330 0666

Emergency Telephone Number: 0421 277 889

16. Other Information

Revision Date:	July 1, 2014
Revision Number:	2
Supersedes:	January 6, 2012
Indication of Changes:	Updated supplier address, Section 1.3.
-	Updated in accordance with the provisions of OSHA 1910.1200 App D and REACH
	Annex II (EU No 453/2010). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.