

- Seals out Water, Sewer Gases, and Rodents From Conduits
- Installs in 45 Seconds
- Easy to Re-Enter
- Holds up to 10' of Water-Head Pressure
- One Kit Seals Six 2" (50mm) Conduits
- Compatible with Cables and Conduits
- Complies with TIA-758-B Standard 5.1.1.2.8, 5.4.2.3 and 7.4.2.8.1 Sealing Ducts




Open-Celled Canned Foams & Duct Putty

- Do Not Hold Water-Head
 Pressure
- Do Not Fully Cure in Conduits
- Sag and Dry Out Over Time



Polywater[®] ZipSeal[™] Duct Sealant

ZipSeal^{TD} Duct Sealant is a practical and efficient way to seal innerducts and conduits. The revolutionary Zip-Disc insert and unique two-part foam installs quickly and effectively. This innovative design Mixing Nozzle allows for horizontal and vertical installation with minimal drippage. The foam can be removed in just minutes. ZipSeal[™]can hold up to 10 feet of water-head pressure.



Horizontal application

| Cat. No. | Package Components | Case Qty |
|-------------|--|----------|
| ZIP-50KIT1 | 1 50mL two-part foam sealant cartridge w/ resealing cap, 2 static mixing nozzles, 2 pairs disposable gloves 5 2" Zip-Discs | 1 |
| ZIP-50KIT1G | ZIP-50KIT1 w/ dispensing tool | 1 |
| ZIP-KITB6 | 6 ZIP-50KIT1 | 6 |
| T00L-50-11 | Dispensing tool | 1 |
| MXR-20T-10 | Mixing nozzles | 10 |

suitable for the intended use.



Vertical application

2-Part

Zip-Disc

To view technical information on our website, go to www.polywater.com/zipseal.html

For application videos

www.polywater.com/videos.asp



ADHESIVES | CLEANERS | LUBRICANTS | SEALANTS

any loss, injury, or direct, indirect, or consequential damages resulting from product's use, regardless of the legal theory asserted

Important Notice: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and

accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only

obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for

WWW.POLYWATER.COM

phone: 1-800-328-9384 1-651-430-2270 fax: 1-651-430-3634 email: support@polywater.com

11222 60th Street North, Stillwater, MN 55082, U.S.A.